

24 FIBRE OPTICAL FIBRE ENCLOSURE MEDIUM

This IP65 lockable enclosure offers the ability to terminate 24 fibres housed in a strong, robust, ABS enclosure for indoor and outdoor applications. The enclosure can accept a number of adaptor types, with two outgoing and one incoming cable entry points that are sealed to ensure the IP65 rating is protected once installed. There are integrated cable tie positions and fibre bend radius protection. Both the front lockable door and splice tray are detachable to enable easy installation.

FEATURES

- Supports up to IP65
- Supports up to (6 x SC Duplex - 12 fibres) or (6 x LC Quad - 24 fibres)
- APC variants available
- Hinged / removable splice tray assists installation
- Multiple adaptor options available
- Secure lockable front door
- Supplied with fibre transit tubing wall fixings and tie wraps
- Integrated bend radius



TECHNICAL SPECIFICATION

Height - Width - Depth	258mm x 186mm x 61mm
Net weight	0.85kg
Material	ABS
Cable Entry	1
Cable Exit	2
IP Rating	IP65
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1

Part Number: **FE-IP65-6-SC-DPX-MED-HINGE**